ELIMINATE DEPOSITS WITH AIR-POWERED PERFORMANCE

FOR TUBES 1" I.D. AND UP



AWT-100X Air-powered Performance

The AWT-100X has power and versatility to clean virtually any tube or pipe in either wet or dry modes (see page 18 for details on the Dry Pickup Attachment and Vacuum). You control the speed and torque of the unit's flexible shaft to suit your application.

A variety of cleaning tools are available for the different kinds of deposits you face. For superior air-powered technology that handles all your tough cleaning applications, this unit will blow you away.

AWT-100X	
Motor Power	Up to 4 HP depending upon air pressure and volume
Air Requirements	Minimum 60 PSI at 85 CFM, Maximum 100 PSI at 130 CFM
Flexible Shaft Speed	Adjustable, 500-3,000 rpm
Water Requirements	Minimum 30 PSI at 3 GPM
Dimensions	37" high x 20" wide x 17" deep
Weight	54 lbs net dry

FEATURES

- Air-powered
- Stainless steel construction
- Air lubricator
- Speed/torque control to set shaft rotation to optimum speed for each application
- Quick connect threadless shaft manifold
- Interchangeable cleaning tools
- Integrated dolly
- · Simultaneous water flush
- Foot switch activation

RECOMMENDED

ASH-B50-G: Air Supply Hose, 1/2" x 50' Call for Price

CONTRACTOR DOLLY

The AWT-100X is available with an integrated contractor dolly for total mobility at multiple job locations.

RAM-DOLLY-C: Heavy-Duty Contractor Dolly... **Call for Price Note:** Available for upgrade with a machine.







